



Multi-flow selectable nozzle QUADRAFOG



QUADRAFOG nozzles with a wide range of capacities; working pressure from 3 to 40 bar.

Made of hard anodized aluminum and ultra-resistant plastic material.

Ball shut-off valve, made of stainless steel with easy-to-replace self-lubricating seals. Pistol grip with non-slip finish mounted under the valve. Full (central), atomized (protects the operator by significantly reducing the temperature) and fractional jet selector; selectable purge position without blocking the water flow. Minimal maintenance needed.

FEATURES AND MODELS AVAILABLE :

Model	Weight	Flow rate (l/min)	Pressure	Thread	PN
QUADRAFOG <i>DQ40</i>	1,0 kg	20 - 40 - 90 - 150	3/20 bar	1" (UNI 25)	16
QUADRAFOG <i>DQ60</i>	1,0 kg	20 - 40 - 90 - 150 - 230	3/20 bar	1" (UNI 25)	16
QUADRAFOG <i>FQ125P</i>	1,6 kg	110 - 230 - 360 - 470	3/20 bar	1,5" (UNI 45)	16
QUADRAFOG <i>QF150-HP</i>	1,0 kg	20 - 40 - 100 - 150	6/40 bar	1" (UNI 25)	40
QUADRAFOG <i>QF235-HP</i>	1,6 kg	20 - 40 - 90 - 150 - 235	6/40 bar	1" (UNI 25)	40

Low or medium expansion foam adapters available on request for each model.

Conformity : EN 15182 -2/4 type 3

WARRANTY 5 YEARS