

## UE TFT Foam Eductor 60 GPM



Equipped with 1.5" Female x 1.5" Male connections, complete with suction tube and rotating mixing selector with positions of: closing (OFF) and mixing at **0,25% - 0,5% - 1% - 3% - 6%**.

Made of an anti-corrosion aluminium alloy, it is extremely small and light, weight without fittings: kg. 2.00 designed for easy use with gloves.

### Features

Mixing percentage indicators made on the mixer head, easy to select and easy to read, allow the accurate mixing of various foaming agents with percentages ranging from 0.25% to 6%.

The mixer is equipped with a suction pipe with a stainless steel terminal.

Designed for use with all types of foams, it is particularly suitable for new class A / B foaming agents with low mixing percentages. The mixer has two unique features: the "*backslash*" function button allows easy washing of the foam residue from the mixer, ensuring excellent functionality during the next operation.

"*Quick Release Locker*" function: allows the mixer body to be detached from the dosing head for easy maintenance and cleaning.

The optimal operating pressure is 10/11 bar, minimum pressure 8 bar

Available in the following versions:

UE-060 - flow 227 LPM / cod. **10.0112.045**

UE-095 - flow 360 LPM / cod. **10.0112.046**

UE-125 - flow 473 LPM / cod. **10.0112.047**

## WARRANTY 5 YEARS