



## Selectable Gallonage Nozzle mod. THUNDERFOG



THUNDERFOG model selectable flow nozzle.

With five flow settings: 360 - 470 - 570 - 750 - 950 l / min at 7 bar.

Made of lightweight materials: hard-coated anodized aluminum.

Fixed tooth head covered in shockproof soft rubber with jet adjustment: full, fractionated, nebulized.

Quick change rear valve seat and slide valve system in stainless steel.

Pistol grip with opening and closing lever.

NFPA / FM certification.

The nozzle is equipped with a 2.5" female connection (UNI 70).

**Cod. 10.0302.027**

*(cod. TFT: JTS250PE)*



## Nozzle with dual handle THUNDERFOG PLAYPIPE



The smallest and most compact dual handle nozzle available on the market, compatible for use on 64mm or 76mm (2.5" or 3") lines.

Selectable flow nozzle with five flow settings: 360 - 470 - 570 - 750 - 950 l / min at 7 bar.

Made of hard anodized aluminum, with high resistance chemical and saline solutions. Fixed tooth head covered in shockproof soft rubber with jet adjustment: full, fractionated, nebulized.

Quick change rear valve seat and slide valve system in stainless steel.

With opening and closing lever.

Side handles for double grip, designed to reduce operator fatigue, allows use in pairs. NFPA / FM certification.

The lance is equipped with a 2.5" female connection (UNI 70).

**Cod. TFT:** JTS250PPF