



## The right angle Torch ATEX "ZONE 0" L-90 POWER

Light, small and easy to operate. It incorporates our famous LED Engine optics, including 3 LEDs to generate spot and flood lighting options, combined with Step Lighting function to illuminate the path. Certified ATEX 'ZONE 0' for use in explosive atmospheres.

- **Power LED Engine** optics with 3 LEDs
- Spot, flood and stroboscopic options
- **Step Lighting System**: a light beam projected directly into the ground to illuminate the path
- **BOOSTER** function for high penetration
- Up to **340 lumens** in high intensity mode
- Low intensity mode available
- **Backlit button**: indication of the light duration and battery level
- Low battery warning: flashes 15 min. before turn off
- **Photoluminescent bezel** (optional)
- Ring and spring **clip** in the back
- Chargers for 1, 2, 3 or 5 torches (only for rechargeable model)



It's available in 2 versions :

- L-90 POWER with 3 AAA alkaline batteries (included)  
**Cod. 20.0302.017**
- L-90R POWER with Li-ion rechargeable battery / 3,7 V (included) - *can be used with alkaline batteries*  
**Cod. 20.0301.030**



### Features :

- Certified **ATEX ZONE 0 (GAS)**
- II 1G Ex ia op is IIC T4 Ga
- Protection degree: **IP67**
- Measures: 73 x 71 x 158 mm.
- Weight: alkaline model: **340 gr.** (batteris AAA included); rechargeable model: **290 gr.** (battery included)
- Burning time: alkaline model **10 hours** (saving mode 20h); rechargeable model **4 hours** (saving mode 18h)
- Lighting source: L-90P **300 lumen**, up to 255 meters; L-90RP **340 lumen**, up to 265 meters
- Thermoplastic resin with high resistance to the impacts, extreme temperatures and corrosive substances.
- Antistatic
- Battery: AAA 3 batteries (included); Li-ion | 3,7 V

Battery charger sold separately available in versions:  
standard (100-240 V) **cod. 30.0401.023**  
for vehicle (12-24 V) **cod. 30.0401.024**

The lamp comes equipped with a jacket **clip** and a **hook and loop**.

