



The right angle Torch ATEX "ZONE 0" L-90

Light, small and easy to operate. It incorporates our famous LED Engine optics, including 2 LEDs (spot, flood and step light options). It easily adapts to the firefighter's tunic. It is certified **ATEX ZONE 0** for use in explosive atmospheres.


- LED Engine optics with 2 LEDs
- Spot, flood and stroboscopic options
- Step Lighting System: a light beam projected directly into the ground to illuminate the path
- BOOSTER function for high penetration
- High and low intensity modes
- Backlit button: indication of the light duration and battery level
- Ring and spring clip in the back
- Neodymium magnet (optional)
- Photoluminescent bezel (optional)
- Chargers for 1, 2, 3 or 5 torches (only for rechargeable model)

It's available in 2 versions:

- ➤ L-90 with 3 AAA alkaline batteries (included) Cod. 20.0302.016
- ➤ L-90R with Li-ion rechargeable battery / 3,7 V (included) can be used with alkaline batteries Cod. 20.0301.029

Features:

- Certified ATEX ZONE 0 (GAS)
- II 1G Ex ia op is IIC T4 Ga
- Protection degree: IP67
- Measures: 73 x 71 x 158 mm.
- Weight: alkaline model: 340 gr. (AAA batteries included);
 rechargeable model: 290 gr. (battery included)
- Burning time: alkaline model 10 hours (saving mode 20h);
 rechargeable model 4 hours (saving mode 18h)
- Lighting source: L-90 250 lumen, up to 220 meters;
- L-90R 280 lumen, up to 235 meters
- Thermoplastic resin with high resistance to the impacts, extreme temperatures and corrosive substances.
- Antistatic
- Battery: AAA 3 batteries (included); Li-ion | 3,7 V



Battery charger sold separately available in versions: standard (100-240 V) cod. 30.0401.023 for vehicle (12-24 V) cod. 30.0401.024

The lamp comes equipped with a jacket clip and a hook and loop.

