

## HALFMASK POLIMASK WITH ANTI-SMOKE FILTER



The **Polimask 2000** model **ALFA** is a one size half mask complying with EN 140. It is equipped with standard screw in connector according to EN 148/1 for use with on DIREN series filter. Suitable for forest fire protection equipment.

- The **seal** round the nose has been improved thanks to a folding groove which adapts all nose shapes. **Polimask 2000** can be used by operators who wear glasses as they do not interfere with the seal of the half mask and in the meantime the exhaled air expelled to the external atmosphere do not cause the misting of the lense.
- The **front frame** allows a floating sealing. The elastic harness is inserted into a stiff part fastened to the exhalation valve group which covers the mouth. The elastic strength of the harness is uniformly distributed on the face seal which is able to float and guarantee a perfect sealing.
- The **harness** is made of an elastic fabric which does not capture the hair, does not cause a bothersome sensation of warmth on the skin of the neck. The four adjustments of the front frame are self-regulating. The harness can be adjusted by the operator pulling or loosing the straps through the end buckles located on the neck. This way the operator will never have the final part of the harness in front of the facepiece thus allowing a free vision field.

Available in EPDM and in SILICONE RUBBER.  
Complying with EN 140 III cat. D.lgs.475 of 4.12.1992 and EN 143 (Filters).

POLIMASK 2000 ALFA in EPDM: **code 80.0502.007**