



Modular mobile Tank with rigid structure



Modular mobile tank with rigid structure (divisible pedestals), polygonal shape to:
6 sides - up to 3500 liters
8 sides - from 6000 to 8000 liters
12 sides - from 12000 to 20000 liters
16 sides - from 30000 liters

Available volumes from 1,000 liters to 42,000 liters.

Available version with padding of the edge for the upper protection of the cloth.

Heat-sealed SHEET in one piece
Backing fabric (DIN 60 001) PES (Polyester)
PVC coating (cadmium free)
Glossy lacquered finish
Thickness > mm 0,55
Weight (DIN EN ISO 2286-2) > gr/sqm. 650
Tear resistance and tearing
Resistance to cold, heat and flame
CASTINGS (upper connection joints and lower support plates) in UNI 5079 light alloy, with electrocolor anodizing
Decomposable FRAME in light alloy with antioxidant treatment
Extruded tubular external / internal dimensions mm. 40/32
Hardness HB 100 +/- 5%
Antioxidant treatment with silver anodizing.



The tank is equipped complete with :

- bottom drain with UNI 45 outlet gate tap (the tap can be connected to the cloth by means of a Storz fitting that can be operated with bare hands)
- shaped pipe for the load from above connected UNI 45
- baby carrier with safety pins for frame assembly
- tap bag
- carrying bag and frame holder

Accessories on request :

- UNI 70 fittings
- Storz fittings
- second exhaust UNI or Storz
- carpet (made with the same fabric as the cloth)

The cloth can be customized with logos and / or writings.

The tank is built in compliance with the following standards :

Directive 2006/42/EC

Directive 2001/95/EC

UNI EN ISO 12100-1:2010

