



Fire Proximity Suit A.M.



Designed and manufactured for the Italian Air Force.

Aluminized fire-approach suit composed of:

A.M. JACKET

Designed with a rear pouch to house the breathing apparatus (cylinder carrier).

Mandarin collar with flame-retardant Velcro® throat guard closure.

Front closure with aramid/brass quick-release zipper covered by a flap secured with flame-retardant Velcro®.



A.M. TROUSERS

Front fly with aramid/brass zipper closure.

Equipped with elastic, adjustable braces with buckles; reinforced knees with double-layer fabric.

Available sizes: S / M / L / XL / XXL / 3XL

Suit available in 2 fabrics:

SAFAL EVO 460 gr.

(70% para-aramid 30% Twaron)
lining 100% FR cotton - 160 g.

cod. 80.0106.170 SE

SAFAL GREEN 340 gr.

(50% para-aramid 50% Panox)
Internally insulated with OXISTOP
fabric - 325 g.

cod. 80.0106.141 SG+OXI

STANDARDS

UNI EN ISO 13688:2013

UNI EN 11612:2015

III Category PPE



SAFAL EVO

Protection Levels

A1-B2-C4-D3-E3-F2

SAFAL GREEN

Protection Levels

A1-B2-C4-D3-E3-F2

The suit is supplied with a black PVC holdall bag.



Optional accessories available upon request:

S50/35 Heat-Resistant 5-Finger GLOVE

Palm made of fabric composed of 85% para-aramid fiber (Kevlar) and 15% polyamide, bonded to felt (50% FR viscose + 50% chlorofiber).

Lined with flame-retardant non-woven fabric.

Back and cuff available in:

- SAFAL EVO 460 g (70% para-aramid 30% Twaron), with 160 g FR cotton lining.
- SAFAL GREEN 340 g (50% para-aramid 50% Panox®), internally insulated with OXISTOP 325 g composed of: Pre-oxidized fiber felt (200 g), quilted with lining made of 50% aramid + 50% FR viscose (125 g).



One size (10) – 35 cm gauntlet:

cod. 80.0301.050 ^{SE} - **cod. 80.0301.028** ^{SG+OXI}

S111 INTEGRAL HOOD

Made of:

- SAFAL EVO 460 g (70% para-aramid 30% Twaron with 160 g FR cotton lining.
- SAFAL GREEN 340 g (50% para-aramid 50% Panox®), internally insulated with OXISTOP 325 g composed of: Pre-oxidized fiber felt (200 g), quilted with 50% aramid + 50% FR viscose lining (125 g).

Equipped with elastic underarm straps and adjustable closure with flame-retardant Velcro®.

cod. 80.0106.157 ^{SE} - **cod. 80.0106.031** ^{SG+OXI}

The hood is suitable for use with full-face masks and breathing systems.

Fitted with replaceable panoramic visor in gold-plated or clear 4 mm polycarbonate, certified **EN 166 – EN 136**; internal adjustable helmet compliant with **EN 397**.



MADE IN ITALY